

2.4Ghz 300Mbps WiFi Range Extender

N300, 1-Port, Wall-plug

Model: 7W311



Introduction:

7inova 7W311 is a special costdown version wifi range extender for economic use. With classic design, it has signal strength indicator for best installation place remind, which help boost your existing WiFi network to places out of reach of your existing WiFi.

Easy to setup with any type router

Press the WPS button on your router and the Range Extender button on 7W311 within 2 minutes to finish setup, get quick and secure connection.

More AP and Client mode as you need

7W311 also can turn Ethernet port in your hotel room into your own personal Wi-Fi hotspot, create a New Wi-Fi Network. Moreover, this device additionally supports Client Mode, so you can integrate LAN based devices into your wifi network.

Signal indicator to find the best location

7W311 additionally has intelligent LED indicator, it assists you with the best location indicator with a simple, color-coded light.

Features:

- Deliver 300Mbps wireless speed, work with any 2.4Ghz wireless router
- Create one new Wi-Fi connectivity for up to 1 wired device like a Smart TV, Blu-ray player or game console
- Simple , color-coded light smartly indicate the perfect location
- Compact size but powerful in extending Wi-Fi range

Specification:

Standard	802.11/b/g/n, MIMO technology
Memory	64Mbit(8MByte)
Flash	16Mbit(2MByte)
Interface	1 * 10/100 RJ45 LAN Port
	1 * WPS/ Reset button
LED Light	Power / Ethernet/ Wireless on/off
Antenna	Internal Omni Antenna
Power Supply Unit	100v-240v AC
Power consumption	3W
Frequency	2.4-2.4835GHz
Wireless Transmit Power	14 ~18dBm (Typical)
Wireless Signal Rates	11n: Up to 300Mbps(dynamic)
	11g: Up to 54Mbps(dynamic)
	11b: Up to 11Mbps(dynamic)
Modulation	OFDM = BPSK,QPSK, 16-QAM, 64-QAM
	DSSS = DBPSK, DQPSK, CCK
Throughput	300 Mbps
Operation mode	WiFi Repeater, Wireless AP, Client
Wireless Security	64/128-bit WEP, WPA / WPA2, WPA-PSK/ WPA2-PSK encryption
WPS	PIN.PBC
Package Contents	300Mbps WiFi range extender Quick Installation Guide
System Requirements	Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 7, Windows 8, Windows 10, MAC OS, NetWare, UNIX or Linux
Environment	Operating Temperature: 0~40 °C (32 °F ~104°F) Storage Temperature: -40~70 °C (-40 °F ~158°F) Operating Humidity: 30%~90% non-condensing; Storage Humidity: 30%~95%non-condensing